

Wax Ribbon SY-CP

General purpose Premium Wax Ribbon used for a wide variety of labels. It offers excellent print quality and high density at low temperature levels, and high print speeds of up to 250mm/sec. This Ribbon serves a wide range of printers and materials, including food contact.

Print Head

Type:

Flat Head

Applications:

Shipping labels, inventory labels, general ticketing, retail labels and tags, pharmaceutical labels etc.

Recommended substrates:

Coated papers, uncoated papers, gloss paper, synthetic papers, tags, various types of film, PET label, nylon.

technical specifications

Wax Ribbon SY-CP

Recommended Substrates Characteristics

Nylon	★ ★ ★
Synthetic papers	★ ★ ★ ★
Coated papers	★ ★ ★ ★ ★
Uncoated papers	★ ★ ★ ★ ★
Gloss paper	★ ★ ★ ★ ★
Paper tags	★ ★ ★
Various types of film	★ ★
PET labels	★ ★

Ribbon Specifications

Black coating	Silicone based
Film thickness	0.0045mm +/- 0.0005
Ribbon Thickness	0.008mm +/- 0.0005
Paint type	Wax
Ink melting point	68°C


Typical Compliance

REACH-SVHC free


RoHS - Restriction for Certain Hazardous Substances Halogen Free

TSCA - Control of toxic substances Contact with food

Printing speed



Energy range




Resistance


Scratch



Stain



Chemical



Heat



Expiration Date of the Product:

6 months after the invoice date.

Contact

phone [+ 55 11] 4161 8800

email vendas.syp@syntpaper.com.br

www.syntpaper.com.br