Resin Ribbon SY-R

It is a resin Ribbon that can print on a wide variety of substrates and at low temperature levels. Especially with good resistance to friction.

Printhead Type

Flat Head / Near Edge

Applications

Shipping labels, inventory labels, general tickets issue, retail labels and tags, pharmaceutical labels, hospital use labels, identification cards, fixed asset labels, flexible packaging, price tags, laboratory labels, etc.

Recommended substrates

Coated papers, uncoated papers, gloss paper, synthetic papers, tags, various types of film, PET label, nylon.

technical specifications

Resin Ribbon SY-R

Recommended Substrates Nvlon *** **** Synthetic papers *** Coated papers *** Uncoated papers Gloss paper * * * Paper tags * * * **** Various types of film PET labels ****

Printing Speed Description Speed Low Med High

Ribbon Specifications

Black coating	Non-silicone based	
Film thickness	0,0045mm +/- 0,0005	
Ribbon Thickness	0,008mm +/- 0,0005	
Paint type	Resin	
Ink melting point	-	

Scratch	0	20	40	60	
Stain	0	20	40	60	
Chemical	0	20	40	60	

Resistance

Heat

Typical Compliance

REACH-SVHC free

RoHS – Restriction for Certain Hazardous Substances Halogen Free

TSCA - Control of toxic substances

Expiration Date of the Product:

Consensation of the state of th



phone [+ 55 11] 4161 8800 email vendas.syp@beontag.com



