

# White Matte Vinyl SY-2002

## Application:

Promotional vinyl for short duration with application on flat surfaces, event stands, indoor and outdoor environments, frontlight, promotional adhesive, POS customizations, signage and etc. Not suitable for application on rough and also highly durable surfaces.

## Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies

# White Matte Vinyl SY-2002

White Matte Vinyl SY-2002		
FRONT	PVC FILM	WHITE MATTE MONOMERIC
	GRAMMAGE	80 (+/-10%)
	THICKNESS	80 (+/-10%)
ADHESIVE	DESCRIPTION	TRANSPARENT SOLVENT
	GRAMMAGE	20 (+/-15%)
	TEMPERATURE (°c)	Min.10
	HEAT RESISTANCE (°c)	Max +80
	COLD RESISTANCE (°c)	Max.-10
LINER	PVC FILM	White siliconized paper on one side
	GRAMMAGE	120 (+/-10%)
	THICKNESS	112 (+/- 10%)
Print	Solvete, Eco-Solvent, sérigraphie, Latex and UV	
Clipping	Manual	
Durability	6 months if stored properly	
°C storage	15° C to 30° C humidity 50 to 70%	

## Contact

phone [+ 55 11] 4161 8800  
email [sign@syntpape.com.br](mailto:sign@syntpape.com.br)

[www.syntpape.com.br](http://www.syntpape.com.br)

SYNTPAPER  
**SYP**

SYNTPAPER  
**SYP**