

Matte White Vinyl SY-2003

0,08/120 GRS

Application:

Promotional vinyl for short duration with application on flat surfaces, event stands, indoor and outdoor environments, frontlight, promotional stickers, POS customizations, signage and etc. Not suitable for application on rough and also highly durable surfaces.

Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies

Contact

tel [+ 55 11] 4161 8800
email vendas.syp@beontag.com

www.syntpapper.com.br



Matte White Vinyl SY-2003

Matte White Vinyl SY-2003		
FRONT	PVC FILM	WHITE MATTE MONOMERIC
	THICKNESS (micron)	80 (+/-10)
ADHESIVE	DESCRIPTION	TRANSPARENT SOLVENT
	TEMPERATURE (°C)	Min.10
	HEAT RESISTANCE (°c)	Max +70
	COLD RESISTANCE (°c)	Max. -20
LINER	PVC FILM	White siliconized paper on one side
	WEIGHT (g/m)	120 (+/-10)
Printing	Solvette, Eco-Solvent, Screen Printing, Latex and UV	
Sample	Manual	
Durability:	6 months, if stocked correctly	
Storage °C	20° C to 30° C humidity 45 to 55%	

