

Matte Black Vinyl SY-2193

Application:

Internal or external use, indicated for long-term exposures, due to its product stability can be applied on almost all surfaces, such as, mobile media such as cars and subways, commercial displays, promotional, display screens, automatic machines.

Additional information:

1. Flat film, low shrinkage rate, elasticity and weather resistance
2. Easy to shape
3. Stable product, can be applied to most of the surface
4. High Quality Solvent-Based Glue

Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies.

Contact

tel [+ 55 11] 4161 8800
email vendas.syp@beontag.com

www.syntpape.com.br



Matte Black Vinyl SY-2193

Matte Black Vinyl SY-2193		
FRONT	PVC FILM	MONOMERIC MATTE BLACK
	THICKNESS (micron)	80 (+/-10)
ADHESIVE	DESCRIPTION	Solvent-based adhesive
LINER	PVC FILM	Paper with coat coating on one side
	GRAMMAGE (g/m)	120 (+/-5)
Clipping	Manual	
Durability	2 to 3 years	
Storage °C	20° C to 30° C humidity 45 to 55%	

