

# Perforated Vinyl – SY-2310t

## Application:

Ideal for applications in short and medium term visual communication pieces, such as vehicle windows, shop windows, glass in general and other flat transparent surfaces that need light to pass through.

After printing, the image becomes visible due to the blocking of light caused by the black background, however, the perforations allow light to pass through.

## Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by competent bodies.

## Contact

phone [+ 55 11] 4161 8800  
email [sign@syntpaper.com.br](mailto:sign@syntpaper.com.br)

[www.syntpaper.com.br](http://www.syntpaper.com.br)



# Perforated Vinyl – SY-2310t

Perforated Vinyl – SY-2310t		
FRONT	PVC FILM	PERFORATED MONOMERIC FLEXIBLE
	GRAMMAGE	120 (+/-10%)
	HOLE SPACING	40%
ADHESIVE	DESCRIPTION	TRANSPARENT SOLVENT
	GRAMMAGE	20 (+/-15%)
	TEMPERATURE (°c)	Min.10
	HEAT RESISTANCE (°c)	Max +80
	COLD RESISTANCE (°c)	Max.-10
LINER	PVC FILM	White siliconized paper on one side
	GRAMMAGE	140 (+/-10%)
	THICKNESS	132 (+/- 10%)
Print	Solvete, Eco-Solvent, Latex and UV	
Clipping	manual, electronic	
Durability	1 year if stored properly	
°C storage	22° C humidity 50 to 55%	

