

# Matte White Vinyl SY-4003

0,08/120 GRS

## Application:

Coating for wall or ceiling decoration, on a flat surface, event stands, indoor and outdoor environments, frontlight, promotional stickers, POS customizations, signage and etc. Not suitable for application on rough surfaces.

## Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies

## Contact

tel [+ 55 11] 4161 8800  
email vendas.syp@beontag.com

[www.syntpapper.com.br](http://www.syntpapper.com.br)



# Matte White Vinyl SY-4003

Matte White Vinyl SY-4003		
FRONT	PVC FILM	WHITE MATTE MONOMERIC
	THICKNESS (micron)	80 (+/-10)
ADHESIVE	DESCRIPTION	TRANSPARENT SOLVENT
	TEMPERATURE (°C)	Min.10
	HEAT RESISTANCE (°c)	Max +70
	COLD RESISTANCE (°c)	Max. -20
LINER	PVC FILM	White siliconized paper on one side
	WEIGHT (g/m)	120 (+/-10)
Printing	Solvette, Eco-Solvent, Screen Printing, Latex and UV	
Sample	Electronic and Manual	
Durability:	1 year if stored properly	
Storage °C	20° C to 30° C humidity 45 to 55%	

