

Sandblasted Vinyl - SY-4005

Application:

Sandblasted vinyl is an adhesive suitable for lamination, signage, decoration and for environments that need privacy protection in internal and external glass!

Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies

Contact

phone [+ 55 11] 4161 8800
email sign@syntpapel.com.br

www.syntpapel.com.br

SYNTPAPER
SYP

Sandblasted Vinyl - SY-4005

| Sandblasted Vinyl - SY-4005 | | |
|-----------------------------|------------------------------------|-------------------------------------|
| FRONT | PVC FILM | Transparent matte polish |
| | GRAMMAGE | 100 (+/-10%) |
| | THICKNESS | 100 (+/-10%) |
| ADHESIVE | DESCRIPTION | TRANSPARENT SOLVENT |
| | GRAMMAGE | 20 (+/-15%) |
| | TEMPERATURE (°c) | Min.10 |
| | HEAT RESISTANCE (°c) | Max +80 |
| | COLD RESISTANCE (°c) | Max.-10 |
| LINER | PVC FILM | White siliconized paper on one side |
| | GRAMMAGE | 140 (+/-10%) |
| | THICKNESS | 132 (+/- 10%) |
| Print | Solvete, Eco-Solvent, Latex and UV | |
| Clipping | Manual, electronic | |
| Durability | 1 year, if stored properly | |
| °C storage | 22° C humidity 50 to 55% | |

SYNTPAPER
SYP