

Floor Lamination - SY-4210

0,18/120 GRS

Application:

- Anti-skid, anti-friction, image protection and stereoscopic effect;
- Excellent flatness and anti-shrinking, easy to clean and good image appearance, for flat surfaces.
- Indoor use, cold lamination for floor image protection.

Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies

Contact

tel [+ 55 11] 4161 8800
email vendas.syp@beontag.com

www.syntpapper.com.br



Floor Lamination - SY-4210

Floor Lamination - SY-4210

FRONT	PVC FILM	Transparent matte polish
	THICKNESS (micron)	200 (+/-10)
ADHESIVE	DESCRIPTION	TRANSPARENT SOLVENT
	TEMPERATURE (°C)	Min.10
	HEAT RESISTANCE (°c)	Max +70
	COLD RESISTANCE (°c)	Max. -20
LINER	PVC FILM	White siliconized paper on one side
	WEIGHT (g/m)	120 (+/-10)
Printing	Not applicable	
Sample	Manual	
Durability:	1 year if stored properly	
Storage °C	20° C to 30° C humidity 45 to 55%	

