

# High Gloss Orange Vinyl SY-K04

## Application:

Internal or external use, indicated for long-term exposures, due to its product stability can be applied on almost all surfaces, such as, mobile media such as cars and subways, commercial displays, promotional, display screens, automatic machines.

## Additional information:

1. Flat film, low shrinkage rate, elasticity and weather resistance
2. Easy to shape
3. Stable product, can be applied to most of the surface
4. High Quality Solvent-Based Glue

## Conditions of use:

The user is fully responsible for the suitability of the product for the intended use, we recommend carrying out application tests. Warranties will only be offered through a contract signed between the parties, based on technical tests by the competent bodies.

## Contact

tel [+ 55 11] 4161 8800  
email vendas.syp@beontag.com

[www.syntpape.com.br](http://www.syntpape.com.br)



# High Gloss Orange Vinyl SY-K04

High Gloss Orange Vinyl SY-K04		
FRONT	PVC FILM	MONOMERIC HIGH GLOSS ORANGE
	THICKNESS (micron)	80 (+/-10)
ADHESIVE	DESCRIPTION	Solvent-based adhesive
LINER	PVC FILM	Paper with coat coating on one side
	GRAMMAGE (g/m)	120 (+/-5)
Clipping	Manual	
Durability:	2 to 3 years	
Storage °C	20° C to 30° C humidity 45 to 55%	

