

In Mold Label SY-ML

Matte white BOPP film on one side, for In Mold Label, intended for use in injection molding.

Printing

- Offset
- Flexography
- Silkscreen
- Digital
- Rotogravure

Benefits

- Excellent whiteness
- One side white with high gloss and one side opaque
- Anti-static material
- High resistance to moisture, chemical substances, oils and abrasion.

Applications

Specially developed for in-mold label in PP and PE injection molds.

Supply

Jumbo reel, rolls cut to size.

Contact
phone [+ 55 11] 4161 8800
email vendas.syp@beontag.com

www.syntpaper.com.br



In Mold Label SY-ML

In Mold Label SY-ML				
Properties		Codes	SY-MUL 65	SY-MU 70
Weight		g/m²	36	62,3
Thickness		microns	65	70
Density		g/cc	0,58	0,89
Brightness	Brightness	%	98	64
	Opaque		22	11
Whiteness	Brightness	%	79	88
	Opaque		83	89
Opacity		%	85	89
Surface Tension	Brilho	dyne/cm	39	39
	Opaco		40	40
Roughness	Brilho	microns	0,12	0,17
	Opaco		1,18	1,08
Tensile strength	MD	MPA	53	97
	TD		108	202

Important:

The above information is derived from quality testing for reference only. The buyer must verify if the product is suitable for its intended use before starting the manufacturing or conversion process.

